

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

**AMENDMENTS TO THE CLAIMS**

**LISTING OF CLAIMS**

1. - 2. (Canceled)

3. (Currently Amended) ~~An apparatus for charging a rechargeable lead-acid battery, said apparatus comprising:~~

~~—— generator means for generating a charging current for charging the battery, and an overcharge current increment to be added to the charging current to yield an overcharge current; and,~~

~~—— controller means for controlling said generator means, said controller means including~~

~~—— (a) feedback means for determining at least one of a charge acceptance ability and a state of charge of the rechargeable lead-acid battery during recharging;~~

~~—— (b) overcharge instruction means for determining the overcharge current, the overcharge current exceeding the charge acceptance ability of the battery; and,~~

~~—— (c) current control means for controlling the generator to supply the charging current and the overcharge current increment, the current control means being operable to deliver the overcharge current to the battery during charging; and wherein~~

~~—— the overcharge instruction means is operable to determine an overcharge duration and an overcharge time;~~

~~—— the current control means is operable to deliver the overcharge current to the battery for the overcharge duration at the overcharge time; and~~

The apparatus as defined in claim 22 wherein the overcharge time is determined to be after the state of charge of the lead-acid battery reaches 60%.

4. (Previously Presented) An apparatus for charging a rechargeable lead-acid battery, said apparatus comprising:

generator means for generating a charging current for charging the battery, and an overcharge current increment to be added to the charging current to yield an overcharge current; and,

controller means for controlling said generator means, said controller means including

(a) feedback means for determining at least one of a charge acceptance ability and a state of charge of the rechargeable lead-acid battery during recharging;

(b) overcharge instruction means for determining the overcharge current, the overcharge current exceeding the charge acceptance ability of the battery; and,

(c) current control means for controlling the generator to supply the charging current and the overcharge current increment, the current control means being operable to deliver the overcharge current to the battery during charging; and wherein

the overcharge instruction means is operable to determine an overcharge duration and an overcharge time;

the current control means is operable to deliver the overcharge current to the battery for the overcharge duration at the overcharge time; and

the overcharge duration is between a half minute and five minutes, and the overcharge current exceeds the charge acceptance ability of the lead-acid battery by less than one fifth of the battery capacity and by more than one twentieth of the battery capacity.

5. (Previously Presented) An apparatus for charging a rechargeable lead-acid battery, said apparatus comprising:

generator means for generating a charging current for charging the battery, and an overcharge current increment to be added to the charging current to yield an overcharge current; and,

controller means for controlling said generator means, said controller means including

(a) feedback means for determining at least one of a charge acceptance ability and a state of charge of the rechargeable lead-acid battery during recharging;

(b) overcharge instruction means for determining the overcharge current, the overcharge current exceeding the charge acceptance ability of the battery; and,

(c) current control means for controlling the generator to supply the charging current and the overcharge current increment, the current control means being operable to deliver the overcharge current to the battery during charging; and wherein

the overcharge instruction means is operable to determine an overcharge duration and an overcharge time;

the current control means is operable to deliver the overcharge current to the battery for the overcharge duration at the overcharge time;

the overcharge instruction means determines a plurality of overcharge times, an associated overcharge current for each overcharge time, and an associated overcharge duration for each overcharge time;

the associated overcharge duration for each overcharge time being between a half minute and five minutes; and,

the associated overcharge current for each overcharge time exceeds the charge acceptance ability of the lead-acid battery at the overcharge time by less than one fifth of the battery capacity and by more than one twentieth of the battery capacity.

6. (Original) The apparatus as defined in claim 5 wherein the plurality of overcharge times are after the state of charge of the battery is at least 60% and before the state of charge of the battery is 100%.

7. (Original) The apparatus as defined in claim 6 wherein after the associated overcharge duration for each overcharge time has elapsed, the generator means is operable to supply an associated voltage-stabilizing current to the battery for an associated voltage-stabilizing interval before the charging current is restored, the associated voltage-stabilizing current for each overcharge time being less than a tenth of the battery capacity.

8. (Original) The apparatus as defined in claim 7 wherein the associated voltage-stabilizing interval for each overcharge time is at least five seconds.

9. (Original) The apparatus as defined in claim 7 wherein a total overcharge delivered during charging of the battery is less than 5% of a total charge provided to the battery during recharging.

10. (Original) The apparatus as defined in claim 6 further comprising temperature sensing means for determining an internal temperature of the battery, wherein the overcharge instruction means is operable to adjust the overcharge current depending on the internal temperature of the battery.

11. – 12. (Canceled)

13. (Currently Amended) ~~A method for recharging a rechargeable lead-acid battery, the method comprising:~~

- ~~(a) generating a charging current for charging the battery;~~
- ~~(b) supplying the charging current to the battery;~~
- ~~(c) determining at least one of a charge acceptance ability and a state of charge of the rechargeable lead-acid battery;~~
- ~~(d) determining the overcharge current, the overcharge current exceeding the charge acceptance ability of the battery;~~

~~(e) determining an overcharge current increment to be added to the charging current to yield the overcharge current;~~  
~~(f) during step (b), supplying the overcharge current increment to the battery; and wherein~~  
~~an overcharge duration and an overcharge time is determined;~~  
~~the overcharge current is supplied to the battery for the overcharge duration at the overcharge time; and~~

The method as defined in claim 24 wherein the overcharge time is after the state of charge of the lead-acid battery reaches 50%.

14. (Previously Presented) A method for recharging a rechargeable lead-acid battery, the method comprising:

- (a) generating a charging current for charging the battery;
- (b) supplying the charging current to the battery;
- (c) determining at least one of a charge acceptance ability and a state of charge of the rechargeable lead-acid battery;
- (d) determining the overcharge current, the overcharge current exceeding the charge acceptance ability of the battery;
- (e) determining an overcharge current increment to be added to the charging current to yield the overcharge current; and
- (f) during step (b), supplying the overcharge current increment to the battery; and wherein
  - an overcharge duration and an overcharge time is determined;
  - the overcharge current is supplied to the battery for the overcharge duration at the overcharge time; and
  - the overcharge duration is between a half minute and five minutes, and the overcharge current exceeds the charge acceptance ability of the lead-acid battery by less than one fifth of the battery capacity and by more than one twentieth of the battery capacity.

15. (Previously Presented) A method for recharging a rechargeable lead-acid battery, the method comprising:

- (a) generating a charging current for charging the battery;
- (b) supplying the charging current to the battery;
- (c) determining at least one of a charge acceptance ability and a state of charge of the rechargeable lead-acid battery;
- (d) determining the overcharge current, the overcharge current exceeding the charge acceptance ability of the battery;
- (e) determining an overcharge current increment to be added to the charging current to yield the overcharge current; and
- (f) during step (b), supplying the overcharge current increment to the battery; and wherein
  - an overcharge duration and an overcharge time is determined;
  - the overcharge current is supplied to the battery for the overcharge duration at the overcharge time;
  - a plurality of overcharge times, an associated overcharge current for each overcharge time, and an associated overcharge duration for each overcharge time, are determined;
  - the associated overcharge duration for each overcharge time is between a half minute and five minutes; and,
  - the associated overcharge current for each overcharge time exceeds the charge acceptance ability of the lead-acid battery at the overcharge time by less than one fifth of the battery capacity and by more than one twentieth of the battery capacity.

16. (Original) The method as defined in claim 15 wherein the plurality of overcharge times are after the state of charge of the battery is at least 60% and before the state of charge of the battery is 100%.

17. (Original) The method as defined in claim 16 wherein after the associated overcharge duration for each overcharge time has elapsed, an associated voltage-stabilizing current is delivered to the battery for an associated voltage-stabilizing interval before the charging current is restored, the associated voltage-stabilizing current for each overcharge time being less than a tenth of the battery capacity.

18. (Original) The method as defined in claim 17 wherein the associated voltage-stabilizing interval for each overcharge time is at least five seconds.

19. (Original) The method as defined in claim 17 wherein a total overcharge delivered during charging of the battery is less than 5% of a total charge provided to the battery during recharging.

20. (Original) The method as defined in claim 16 further comprising determining an internal temperature of the battery and adjusting the overcharge current depending on the internal temperature of the battery.

21. (New) An apparatus for charging a rechargeable lead-acid battery, said apparatus comprising:

generator means for generating a charging current for charging the battery, and an overcharge current increment to be added to the charging current to yield an overcharge current; and,

controller means for controlling said generator means, said controller means including

(a) feed back means for determining at least one of a charge acceptance ability and a state of charge of the rechargeable lead-acid battery during recharging;



(b) overcharge instruction means for determining the overcharge current, the overcharge current exceeding the charge acceptance ability of the battery; and,

(c) current control means for controlling the generator to supply the charging current and the overcharge current increment, the current control means being operable to deliver the overcharge current to the battery during charging.

22. (New) The apparatus as defined in claim 21 wherein  
the overcharge instruction means is operable to determine an overcharge duration and an overcharge time; and,  
the current control means is operable to deliver the overcharge current to the battery for the overcharge duration at the overcharge time.

23. (New) A method for recharging a rechargeable lead-acid battery, the method comprising:

- (a) generating a charging current for charging the battery;
- (b) supplying the charging current to the battery;
- (c) determining at least one of a charge acceptance ability and a state of charge of the rechargeable lead-acid battery; and
- (d) determining an overcharge current, the overcharge current exceeding the charge acceptance ability of the battery;
- (e) determining an overcharge current increment to be added to the charging current to yield the overcharge current; and
- (f) during step (b), supplying the overcharge current increment to the battery.

24. (New) The method as defined in claim 23, wherein

an overcharge duration and an overcharge time are determined;  
the overcharge current is supplied to the battery for the overcharge  
duration at the overcharge time.